

# G<sup>®</sup>-ERGO flex

Aluminum picking cart

**NOW** with continuous adjustable spring force!

# GMÖHLING

**NEW**



Click here for the  
G<sup>®</sup>-ERGO flex video



We bring **flexibility** to your logistics!

GMÖHLING Transportgeräte GmbH  
Stadelner Hauptstr. 34 • 90765 Fürth, Germany  
Phone: +49 911 7669 - 0 • Fax: +49 911 7669 - 277  
sales@gmoehling.com

[www.gmoehling.com](http://www.gmoehling.com)

# G<sup>®</sup>-ERGO flex

With continuous adjustable spring force: **The optimal solution for your logistics!**

## ADVANTAGES:

- Individually adjustable spring force depending on the product – fastest work at the highest level!
- Intuitive operation without prior knowledge
- Constant loading and unloading height even with goods of different weights
- Unique on the market
- Made of anodised aluminum - light, robust and abrasion resistant

## SIMPLE OPERATION:

- Spring force easily adjustable – lightly pull the handle upwards and then slide it
- Continuously adjustable in the working process
- Spring force from approx. 25 to 70 kg – continuous adjustment range of approx. 45 kg.
- Flexible adjustment possible at any time



## Technical data

Model number	Wheel arrangement	Dimensions L x W x H (approx. mm)		Volume (approx. l)	Wheel -Ø (mm)	Spring force (approx. kg)	Load capacity (approx. kg)	Weight (approx. kg)	Order no.
		internal	external						
D 5405 ERGO flex	E	1070 x 740 x 610	1180 x 780 x 895	480	125	25 - 70	130	56	022540501
D 5405 ERGO flex grip	E	1070 x 740 x 610	1435 x 780 x 1040	480	125	25 - 70	130	58	222540502


- All-round PVC bumper on the upper edge of the trolley
- With closed base for driving underneath with pallet truck or fork-lift truck
- Wheel arrangement E: 4 swivel castors and one fixed castor, with spring suspension for secure floor contact and good directional stability
- Manufactured according to European standard EN 1757-3
- Option: ergonomic push handle



Narrower gap with plastic rim inlay or brush strip



Ladder, push aid, drink holder, scanner holder, label dispenser, writing tablet or clipboard



Wheel arrangement E: 4 swivel castors, 2 with wheel brakes and 1 fixed castor

## Special solutions

Available on request!  
We respond to your individual wishes and needs, for different dimensions, spring forces, different handles, ladder, bumpers and wheels - contact us.

Individual solutions are our business – We will find **YOUR** solution!

**GMÖHLING**

Certification: DIN EN ISO 9001

G<sup>®</sup>-ERGO flex • 04.2023 • Technical changes reserved



[www.gmoehling.com](http://www.gmoehling.com)